



EUROPEAN INSPECTION AND CERTIFICATION COMPANY S.A.

CERTIFICATE OF CONFORMITY

FULLNESS EXAMINATION OF TECHNICAL FILE

Certificate No. : MA.0747
Issue Date : 03/08/2021
Expiry Date : 02/08/2026
Applicant : FUJIAN SNOWMAN CO., LTD./
(Name & Address) Dongshan Road, Minjiangkou Industrial District, Fuzhou City, Fujian
Province, China.
Manufacturer : Same as Applicant
(Name & Address)
TCF No. : VC-CH-2021051707
Product Description : Shielding Pump
Model(s) : SMTP-750-16DE0.8, SMTP-1100-16DE1.5, SMTP-2200-50DE0.8, SMTP-
3000-50DE1.5, SMTP-3000-80DE0.8, SMTP-5500-80DE1.5
(See Annex I for details)
Directive(s) : Machinery Directive 2006/42/EC
Standard(s) : EN ISO 12100:2010, EN 809:1998+A1:2009/AC:2010, EN 60204-1:2018

This is to certify that, upon the relevant application of the above mentioned applicant, EUROCERT as Third Party Authority has reviewed the Technical Construction File of the described product which found to fulfill the basic health and safety prerequisites of above mentioned Directive(s).

Note:

- The manufacturer should issue a Declaration of Conformity according to the basic requirements of the applicable standards and relevant directives.
- The CE marking can be affixed on the above mentioned product with the manufacturer's responsibility, if all relevant and applicable directives are complied with.
- All modifications to the Technical File should be first submitted to the Third Party Inspection Authority to ensure further validity of this attestation
- This certificate is valid only for the product and configuration described and in conjunction with the technical data detailed above.

Please check the validity of the certificate from our website using the password **Sc5LbRkk**



Third Party Authority Stamp

On Behalf of EUROCERT

GEORGE N. SIFONIOS
Director of Development





EUROPEAN INSPECTION AND CERTIFICATION COMPANY S.A.

Annex I

Certificate No.: MA.0747

Products Specification Table

Type	Max Work Pressure (bar)	Nom. Pressure (bar)	Nom. Power (kW)	Export Flow (L/min)	Voltage (V)	Current (A)	Connection	Ph	Hz	RPM	Duty	INS. Class	Prot.	Weight (kg)
SMTP-750-16DE0.8	25	8	0.75	25	380	2.3	Y	3	50	1410	S1	F	IP55	35
SMTP-1100-16DE1.5	25	15	1.1	25	380	2.8	Y	3	50	1410	S1	F	IP55	40
SMTP-2200-50DE0.8	25	8	2.2	75	380	5.5	Y	3	50	1410	S1	F	IP55	75
SMTP-3000-50DE1.5	25	15	3	75	380	6.8	Y	3	50	1410	S1	F	IP55	90
SMTP-3000-80DE0.8	25	8	3	120	380	6.8	Y	3	50	1410	S1	F	IP55	110
SMTP-5500-80DE1.5	25	15	5.5	120	380	11.8	Y	3	50	1410	S1	F	IP55	130

